## VERTICAL ABOVEGROUND DOUBLE WALL STORAGE TANKS

		EMERGENCY VEN OPENING (PRIMAR	• 0 (
APPROX. CAPACITY (GALLONS)	NOM. DIAMETER	NOM. HEIGHT	
560	48"	6'-0"	
1,000	64"	6'-0"	
2,000	64"	12'-0"	
3,000	84"	10'-6"	
3,000	96"	8'-0"	
4,000	96"	10'-8"	
6,000	96"	16'-0"	
6,000	120"	10'-3"	]
8,000	120"	13'-8"	]
10,000	120"	17'-0"	]
12,000	120"	20'-6"	]
16,500	120"	28'-0"	]
15,000	126"	23'-2"	
15,000	144"	17'-9"	
20,000	144"	23'-8"	
24,000	144"	29'-0"	

Overall tank lengths will vary during actual manufacturing.

## STANDARD SPECIFICATIONS

moderr

- Tank meets UL142 standards for double wall design.
- Modern's standard opening locations and required lifting lugs.
- Exclusive free flow annular space design.
- Exterior coated with one (1) coat of standard shop primer and not blast cleaned
- Check with Modern for type of Emergency Vent Opening supplied.
- Other exterior and interior coating systems available upon request.
- Other tank sizes available upon request.