# Modern Welding Company, Inc.

### Manufacturing Subsidiaries Nationwide

LONG FORM: Section 13205

PRODUCT: Double Wall, Vertical, Aboveground, Fuel Storage Tank

**Guide Specification** 

### **PART I General**

### 1.0 Related Work Specifications:

1.1. Cast-in-Place Concrete: Section 03300

1.2. Anchor Bolts: Section 05501

1.3. Liquid Level Gauges: Section 15174

1.4. Piping: Section 150641.5. Painting: Section 09900

### 2.0 Quality Assurance

#### 2.1 Acceptable Manufacturer:

- A. Modern Welding Company of Owensboro, Inc.
- B. Modern Welding Company of Ohio, Inc.
- C. Modern Welding Company of Iowa, Inc.
- D. Modern Welding Company of Texas, Inc. (Houston)
- E. Modern Welding Company of Texas, Inc. (Rhome)
- F. Modern Welding Company of California, Inc.
- G. Modern Welding Company of Georgia, Inc.
- H. Modern Welding Company of Florida, Inc.
- I. Modern Custom Fabrication, Inc.

### 2.2 Governing Standards:

- A. U.L. 142, Underwriters Laboratories, Inc., "Steel Aboveground Tanks for Flammable and Combustible Liquids".
- B. NFPA 30, National Fire Protection Association, "Flammable and Combustible Liquids Code".
- C. NFPA 30A, National Fire Protection Association, "Code for Motor Fuel Dispensing Facilities and Repair Garages".
- D. Uniform Fire Code, International Fire Code Institute
- E. PEI/RP-200, Petroleum Equipment Institute, "Recommended Practices for Installation of Aboveground Storage Systems for Motor-Vehicle Fueling"

## 3.0 Submittals

safety factor.

3.1 Shop Drawings:				
A. Contractor shall submit copies of shop drawings for each tank. Location of fittings and				
accessories with specific dimensions shall be shown on all drawings.				
3.2 Drawing Approval:				
A. Contractor shall receive drawing approval prior to product fabrication.				
3.3 Catalog Data:				
A. Contractor shall submit current copies of manufacturer's literature.				
3.4 Certification:				
A. Each tank shall bear the U.L. listing mark for, "Secondary Containment				
Aboveground Tank for Flammable Liquids".				
3.5 Installation Instructions:				
A. Contractor shall submit copies of manufacturer's current installation instructions.				
PART II Products				
4.0 Double Wall, Vertical, Aboveground, Storage Tank				
4.0 Double Wall, Vertical, Aboveground, Storage Tank				
4.1 Materials:				
A. Only new material shall be used in the manufacturing process, and the manufacturer shall				
ensure that the material used meets all appropriate specifications and quality assurance				
requirements.				
B. Minimal material thickness of the tank(s) shall be per UL-142 requirements.				
4.2 Dimensions:				
A. Dimensional Requirements:				
<ol> <li>Nominal capacity of the tank(s) shall be gallons.</li> </ol>				
<ol><li>Nominal inner tank diameter of the tank(s) shall be inches.</li></ol>				
<ol><li>Straight shell height shall be approximately feet, inches.</li></ol>				
<ol><li>Minimal material thickness of tank(s) roof shall be</li></ol>				
<ol><li>Minimal material thickness of the tank(s) shell shall be</li></ol>				
<ol><li>Minimal material thickness of the tank(s) bottom shall be</li></ol>				
4.3 Loading Conditions:				
A. Tanks shall meet the following design criteria.				
B. Internal Load:				
1. Tanks shall withstand an air pressure test of 1.5 to 3 psi.				
C. Tank(s) shall be designed to support accessory equipment such as ladders, pumps, floating				
suction, etc. when installed according to manufacturer's instructions and limitations.				
D. Tank(s) shall be provided with suitably designed and located lifting lugs which have a 2:1				

B. Tank(s) shall be secondar venting r C. Tank(s) shall be	e capable of storing liquids will designed for operation at at y tanks shall have openings of equirements as stated in U.L. as capable of storing gasoline, ambient temperatures.	mospheric pressure onl f sufficient size to meet 142, UFC, and NFPA.	ly. Both primary and normal and emergency
5.0 Accessories			
5.1 Certification Plate			
	aboratories label "Secondary shall be affixed to each tank.	Containment Abovegro	ound Tank for Flammable
5.2 Fittings (Threaded			
A. All threaded fi the Unde	ttings shall be of a material of rwriters Laboratories. All fitti closure caps.		·
Qty.	e. Size	Type	Use
5.3 Fittings (Flanged	Nozzles):		
A. All flanged noz	zles shall be of a material of or rwriters Laboratories. All noz		·
Qty.	Size	Туре	Use

4.4 Product Storage Requirements:

### 5.4 Manways:

- A. Manways shall conform to Underwriters Laboratories 142 standard with regard to construction, gaskets and bolting.
- 5.5 Ladders/Walkways:
  - A. Exterior ladder, if necessary, shall be of steel construction and designed using accepted engineering practices.
- 5.6 Fitting, Manway, and Support locations shall be referenced on manufacture drawings.

### **PART III Execution**

#### 6.0 Installation

- 6.1 Testing:
  - A. Tank(s) shall successfully complete an air pressure test of 1.5 to 3 psi prior to installation.
- 6.2 Tank shall be installed in strict accordance with the most recent installation instructions provided by the tank manufacturer, UFC, NFPA, local ordinance, recognized engineering procedure, and other applicable codes.

**FORM: DWVERTAG** 

Modern Welding Company, Inc. Corporate Office (270) 685-4400 2880 New Hartford Road Owensboro, KY 42303

#### **SUBSIDIARIES:**

Modern Welding Company of Owensboro, Inc.

Owensboro, KY (270) 683-5323

Modern Welding Company of Ohio, Inc.

Newark, OH (740) 344-9425

Modern Welding Company of Florida, Inc.

Orlando, FL (407) 843-1270

Modern Welding Company of Texas, Inc.

Houston, TX (713) 675-4211

Modern Welding Company of Texas, Inc.

Rhome, TX (817) 636-2215

Modern Welding Company of Iowa, Inc.

Burlington, IA (319) 754-6577

Modern Welding Company of California, Inc.

Fresno, CA (559) 275-9353

Modern Custom Fabrication, Inc.

Fresno, CA (559) 264-4741

Modern Welding Company of Georgia, Inc.

Augusta, GA (706) 722-3411