MODERN WELDING COMPANY OF TEXAS, INC.

200 N. Main St.

Rhome, Texas 76078 Ph: (817) 636-2215 - Fax # (817) 636-2680 Subsidiary Survey - No. 15

Email: modern15@modweldco.com Website: www.modweldco.com

A. ADMINISTRATIVE PERSONNEL:

Bonnie Scroggins Manager

Wes Ramsey Atmospheric Tank Sales

B. Principal Products and Construction Standards

Manufacturers of underground, aboveground, atmospheric storage tank construction standards include: Underwriter's Laboratories UL-58, UL-1746 and UL-142. Oil water separators are built to Underwriters Laboratories construction standard, UL-2215. Fire rated aboveground storage tanks are built to Underwriter's Laboratories, UL-2085 and Southwest Research Institute fire testing criteria.

Product names include:

- Glasteel™, Glasteel II™, STIP3™, ACT-100, ACT-100-U, underground storage tanks.
- Modern's aboveground "IOC", Integrated Overflow Compartment tanks provide specialized overfill protection.
- STI's, F-921® are double wall aboveground storage tanks.
- FireguardTM and Flameshield, are aboveground fire rated storage tanks.
- Kleerwater™ is Modern's underground and aboveground gravity displacement oil water separator line.
- Modern's AST-10, AST-20 and AST-40 are our complete aboveground fuel dispensing systems designed to meet a variety of fuel handling requirements.

Other recognized tank construction standards include in Modern's product line is the American Petroleum Institute's, API-620, API-650-J and API-650. Tanks can also be built to the American Water Works, AWWA, M-42 and D100 standards.

Storage tanks and vessels can be prepared with special linings or coatings as specified. These special coatings can be for jet fuel or potable water. Other special linings can be rubber or baked phenolic linings for special chemical handling applications.

Other steel fabricated products include: Flotation pontoons for dredging operations, large diameter welded pipe, duct work, bins, hoppers, hydro-pneumatic tanks, potable water tanks, coal and water haulers and underground mining support arches.

- 2.500 tons C. AVERAGE PRODUCTION PER YEAR:
- D. APPROXIMATE PRODUCTION AREA:
 - 1. Inside building 70,000 sq. ft. 2. Outside building 200,000 sq. ft.
- E. MAXIMUM LIFTING AND SHIPPING CAPACITY: 40 tons
- APPROXIMATE RAIL OR TRUCK CLEARANCE OUT OF CITY: F.

Truck 1. Height 16 ft.

2. Width 16 ft.

G. PLATE ROLL CAPACITY: (FOR CARBON STEEL)

1. Width 10 ft. 2. Thickness 1 in.

Heavier rolling available from outside sources.

H. SHIPPING FACILITIES:

1. Truck: Company owned fleet and numerous common carriers

I. TYPES OF MATERIAL WELDED:

- 1. Carbon steel and alloys
- 2. 300 series stainless steel

J. BLAST CLEANING AND COATING FACILITIES:

- 1. Blasting Cleaning facilities. Priming & air-dried coating.
- 2. Outside sources for special coatings, rubber, PVC and lead linings.

K. GENERAL FACILITIES:

- 1. Rotary Shearing & Brake
- 2. Welding Equipment Manual SMAW, submerged arc SAW, GMAW, FCAW and TIG.
- 3. Plasma arc cutting

L. LARGE OUTSIDE STORAGE AREA FOR COMPLETED ITEMS.