Modern Welding Company, Inc.

Manufacturing Subsidiaries Nationwide

LONG FORM: Section 13205

PRODUCT: Double Wall, Vertical, Aboveground, Fuel Storage Tank

Guide Specification

PART I General

1.0 Related Work Specifications:

1.1. Cast-in-Place Concrete: Section 03300

1.2. Anchor Bolts: Section 05501

1.3. Liquid Level Gauges: Section 15174

1.4. Piping: Section 150641.5. Painting: Section 09900

2.0 Quality Assurance

2.1 Acceptable Manufacturer:

- A. Modern Welding Company of Owensboro, Inc.
- B. Modern Welding Company of Ohio, Inc.
- C. Modern Welding Company of Iowa, Inc.
- D. Modern Welding Company of Texas, Inc. (Houston)
- E. Modern Welding Company of Texas, Inc. (Rhome)
- F. Modern Welding Company of California, Inc.
- G. Modern Welding Company of Georgia, Inc.
- H. Modern Welding Company of Florida, Inc.
- I. Modern Custom Fabrication, Inc.

2.2 Governing Standards:

- A. U.L. 142, Underwriters Laboratories, Inc., "Steel Aboveground Tanks for Flammable and Combustible Liquids".
- B. NFPA 30, National Fire Protection Association, "Flammable and Combustible Liquids Code".
- C. NFPA 30A, National Fire Protection Association, "Code for Motor Fuel Dispensing Facilities and Repair Garages".
- D. Uniform Fire Code, International Fire Code Institute
- E. PEI/RP-200, Petroleum Equipment Institute, "Recommended Practices for Installation of Aboveground Storage Systems for Motor-Vehicle Fueling"

3.0 Submittals

safety factor.

3.1 Shop	Drawings:
Α.	Contractor shall submit copies of shop drawings for each tank. Location of fittings and
	accessories with specific dimensions shall be shown on all drawings.
3.2 Drav	ving Approval:
Α.	Contractor shall receive drawing approval prior to product fabrication.
3.3 Cata	log Data:
Α.	Contractor shall submit current copies of manufacturer's literature.
3.4 Cert	ification:
A.	Each tank shall bear the U.L. listing mark for, "Secondary Containment
	Aboveground Tank for Flammable Liquids".
	allation Instructions:
Α.	Contractor shall submit copies of manufacturer's current installation instructions.
PART II Pro	oducts
4.0 Double	Wall, Vertical, Aboveground, Storage Tank
4.1 Mat	erials:
Α.	Only new material shall be used in the manufacturing process, and the manufacturer shall
	ensure that the material used meets all appropriate specifications and quality assurance
	requirements.
В. І	Minimal material thickness of the tank(s) shall be per UL-142 requirements.
4.2 Dim	ensions:
A. D	imensional Requirements:
	1. Nominal capacity of the tank(s) shall be gallons.
	2. Nominal inner tank diameter of the tank(s) shall be inches.
	3. Straight shell height shall be approximately feet, inches.
	4. Minimal material thickness of tank(s) roof shall be
	5. Minimal material thickness of the tank(s) shell shall be
	6. Minimal material thickness of the tank(s) bottom shall be
	ling Conditions:
	anks shall meet the following design criteria.
B. Ir	nternal Load:
	1. Tanks shall withstand an air pressure test of 1.5 to 3 psi.
C. Ta	ank(s) shall be designed to support accessory equipment such as ladders, pumps, floating
	suction, etc. when installed according to manufacturer's instructions and limitations.
D. T	ank(s) shall be provided with suitably designed and located lifting lugs which have a 2:1

- 4.4 Product Storage Requirements:
 - A. Tank(s) shall be capable of storing liquids with a specific gravity up to 1.0.
 - B. Tank(s) shall be designed for operation at atmospheric pressure only. Both primary and secondary tanks shall have openings of sufficient size to meet normal and emergency venting requirements as stated in U.L. 142, UFC, and NFPA.
 - C. Tank(s) shall be capable of storing gasoline, gasohol, jet fuel, avgas, diesel fuel, methanol, or fuel oil at ambient temperatures.

5.0 Accessories

5.1	. Cei	rtific	catic	n P	late	≥:

- A. Underwriters Laboratories label "Secondary Containment Aboveground Tank for Flammable Liquids" shall be affixed to each tank.
- 5.2 Fittings (Threaded/NDT).
 - of

suitable closure	rs Laboratories. All fitti .cans	O	asing threaded plags
B. Fitting Schedule:	cups.		
Qty.	Size	Туре	Use
	s):		
A. All flanged nozzles sh	all be of a material of c		·
A. All flanged nozzles sh the Underwriter	•		·
A. All flanged nozzles sh the Underwriter B. Nozzle Schedule:	all be of a material of c	zles shall be protected	using suitable closure
Fittings (Flanged Nozzles A. All flanged nozzles sh the Underwriter B. Nozzle Schedule: Qty.	all be of a material of c		·
A. All flanged nozzles sh the Underwriter B. Nozzle Schedule:	all be of a material of c	zles shall be protected	using suitable closure
A. All flanged nozzles sh the Underwriter B. Nozzle Schedule:	all be of a material of c	zles shall be protected	using suitable closure
A. All flanged nozzles sh the Underwriter B. Nozzle Schedule:	all be of a material of c	zles shall be protected	using suitable closure
A. All flanged nozzles sh the Underwriter B. Nozzle Schedule:	all be of a material of c	zles shall be protected	using suitable closure

5.4 Manways:

- A. Manways shall conform to Underwriters Laboratories 142 standard with regard to construction, gaskets and bolting.
- 5.5 Ladders/Walkways:
 - A. Exterior ladder, if necessary, shall be of steel construction and designed using accepted engineering practices.
- 5.6 Fitting, Manway, and Support locations shall be referenced on manufacture drawings.

PART III Execution

6.0 Installation

- 6.1 Testing:
 - A. Tank(s) shall successfully complete an air pressure test of 1.5 to 3 psi prior to installation.
- 6.2 Tank shall be installed in strict accordance with the most recent installation instructions provided by the tank manufacturer, UFC, NFPA, local ordinance, recognized engineering procedure, and other applicable codes.

FORM: DWVERTAG

06/2018 Modern Welding Company, Inc. Corporate Office (270) 685-4400 2880 New Hartford Road Owensboro, KY 42303

SUBSIDIARIES:

Modern Welding Company of Owensboro, Inc.

Owensboro, KY (270) 683-5323

Modern Welding Company of Ohio, Inc.

Newark, OH (740) 344-9425

Modern Welding Company of Florida, Inc.

Orlando, FL (407) 843-1270

Modern Welding Company of Texas, Inc.

Houston, TX (713) 675-4211

Modern Welding Company of Texas, Inc.

Rhome, TX (817) 636-2215

Modern Welding Company of Iowa, Inc.

Burlington, IA (319) 754-6577

Modern Welding Company of California, Inc.

Fresno, CA (559) 275-9353

Modern Custom Fabrication, Inc.

Fresno, CA (559) 264-4741

Modern Welding Company of Georgia, Inc.

Augusta, GA (706) 722-3411